

LED T8 Tubes CL

Magnolux LED T8 Tubes are compatible with both, magnetic and electronic ballasts, and are the most efficient and environmentally friendly alternative to traditional fluorescent tubes.





LED T8 Tube CL - EM25-1500

HIGHLIGHTS

- » high energy efficiency
- » lifetime up to 25.000 hours
- » EM and CEM-models are compatibel with magnetic and electric ballast

APPLICATION AREA

Offices, Hotels, Supermarkets, Warehouses, Commercial and Industrial Buildings, Airports, Schools, Hospitals, Parking Decks, etc.











SPECIFICATIONS

Artikel Number Product Name Model

Socket
Lumen Output
Power Consumption
Input Voltage/Hertz

Power Factor Light Color

Color Rendering Index

LED Type Beam Angle Lifetime

Environment Temperature -10°C / +40°C

Material

Product Dimensions

Certificates
PCS/Package
Packaging Size
Weight/Packaging
Product Info

101175

LED T8 Tube CL EM25-1500

G13 - 26 mm 2700 Lumen 25 Watt

85-265 V / 50-60 Hz

>0,95 5500 Kelvin >80

SMD 120° 25000 h -10°C / +4

Alu silver/PC milky Ø 26 mm, L 1500 mm CE, RoHs, EN62471

25

1540 x 215 x 220 mm

22000 g

compatible with magnetic/electronic ballast, use max. 2 tubes

on one ballast