

## LED Panels SL

Magnolux LED Panels of SL Series with their improved luminance are the most efficient and environmentally friendly alternative to traditional ceiling grid lights.



## LED Panel SL - L50-4000-FS-MP

### HIGHLIGHTS

- » available with motion sensor, light sensor and emergency mode for 3 hours
- » dimming with DALI system and with RGB lighting available
- » various frame designs and panel dimensions
- » microprismatic diffusor optional

### APPLICATION AREA

Offices, Schools, Hotels, Banks, Hospitals, Restaurants, Shops, Public Buildings, Entrance Halls, Corridors, etc.

## SPECIFICATIONS

<b>Artikel Number</b>	<b>101764</b>
<b>Product Name</b>	<b>LED Panel SL</b>
<b>Model</b>	<b>L50-4000-FS-MP</b>
Lumen Output	2800 Lumen
LED Power	45 Watt
Power Consumption	50 Watt
Input Voltage/Hertz	220-240 V / 50-60 Hz
Light Color	4000 Kelvin
Color Rendering Index	>80
LED Type	SMD
Beam Angle	120°
Lifetime	50000 h
Environment Temperature	-40°C / +40°C
Material	Alu Flat Frame silver/PC microprismatic
Product Dimensions	295 x 1195 x 9 mm
Certificates	CE
Safety Type	IP40
PCS/Package	1
Packaging Size	1345 x 400 x 44 mm
Product Info	ceiling cut-out 282 x 1182 mm

