

**GRAH**<sup>®</sup>  
LED LIGHTING



**LED Street Lighting LSL - LSL60 I74-4000 (LSV)**

**HIGHLIGHTS**

- » asymmetric distribution of luminosity for optimal lighting
- » optimized heat dissipation extends life time
- » multi layer protection of casing for excellent durability
- » dimming (1-10V) optional

**APPLICATION AREA**

Urban Traffic Roads, Collector Roads, Junctions, Parking Lots, more demanding Industrial Buildings



**SPECIFICATIONS**

|                         |                                                                        |
|-------------------------|------------------------------------------------------------------------|
| <b>Artikel Number</b>   | <b>101556</b>                                                          |
| <b>Product Name</b>     | <b>LED Street Lighting LSL</b>                                         |
| <b>Model</b>            | <b>LSL60 I74-4000 (LSV)</b>                                            |
| Lumen Output            | 8700 Lumen                                                             |
| Power Consumption       | 74 Watt                                                                |
| Input Voltage/Hertz     | 110-250 V / 50-60 Hz                                                   |
| Light Color             | 4000 Kelvin                                                            |
| Lifetime                | 60000 h                                                                |
| Environment Temperature | -30°C / +60°C                                                          |
| Operating Temperature   | +55°C                                                                  |
| Material                | Alu-Die-Casting<br>RAL9006/PMMA                                        |
| Product Dimensions      | 720 x 465 x 139 mm                                                     |
| Product Weight          | 7000 g                                                                 |
| Certificates            | CE, RoHs                                                               |
| Safety Class            | I                                                                      |
| Safety Type             | IP66                                                                   |
| Shock Resistance        | IK08                                                                   |
| Product Info            | light sensor adapter, AA optics asymmetric, excl. pole connection part |