

LED Downlights ST

Magnolux LED Downlights of ST Series with excellent luminance are the most efficient and environmentally friendly alternative to traditional downlights.



LED Downlight ST - R140 30-2080L

HIGHLIGHTS

- » lighting direction adjustable (R70 and R140 models)
- » lifetime up to 50.000 hours
- » various designs with simple white or elegant silver
- » lens or reflector optional

APPLICATION AREA

Private Households, Offices, Commercial and Public Buildings, Industry, Hotels, etc.

SPECIFICATIONS

Artikel Number	101106
Product Name	LED Downlight ST
Model	R140 30-2080L
Lumen Output	2080 Lumen
Power Consumption	30 Watt
Input Voltage/Hertz	110-240 V / 50-60 Hz
Power Factor	>0,8
Light Color	3000 Kelvin
Color Rendering Index	>83
LED Type	COB
Beam Angle	38°
Lifetime	25000 h
Environment Temperature	-25°C / +65°C
Operating Temperature	-25°C / +65°C
Material	Aluminium white/PMMA
Product Dimensions	Ø 150 mm, H 80 mm
Certificates	CE, RoHs
Safety Class	III SELV
Safety Type	IP43
PCS/Package	1
Packaging Size	160 x 160 x 80 mm
Product Info	Ceiling cut-out: 140 mm

