

### LED Downlights ST

Magnolux LED Downlights of ST Series with excellent luminance are the most efficient and environmentally friendly alternative to traditional downlights.





## **HIGHLIGHTS**

- lighting direction adjustable (R70 and R140 models)
- lifetime up to 50.000 hours
- various designs with simple white or elegant silver
- lens or reflector optional

## **APPLICATION AREA**

Private Households, Offices, Commercial and Public Buildings, Industry, Hotels, etc.











# SPECIFICATIONS

# **Artikel Number Product Name** Model

Lumen Output **LED Power Power Consumption** Input Voltage/Hertz

**Power Factor** 

Light Color Color Rendering Index

LED Type Beam Angle Lifetime

Operating Termperature

Material

**Product Dimensions** Certificates Safety Class

Safety Type PCS/Package

Packaging Size Product Info

101264

**LED Downlight ST** R97 7-580

580 Lumen 7 Watt 8.5 Watt

220-240 V / 50-60 Hz

>0.8

>83

3000 Kelvin

COB 60° 50000 h Environment Temperature -25°C / +65°C -25°C / +65°C Aluminium

> white/Aluminium Reflector Ø 105 mm x H 100 mm

CE, RoHs III SELV IP43

> 150 x 150 x 140 mm Ceiling cut-out: 97 mm